
DATA SHEET



Fluorescent Low Range DNA Ladder 50 bp to 1 kb linear scale ready-to-use, orange / blue, green fluorescent

Cat. No.	Amount
M-222S	500 μl (120 ng/μl)
M-222L	5 x 500 μl (120 ng/μl)

Low Range DNA Ladder

	qd	ng/µl
_	1000	10
		10
	600	10
of the local division in which the local division in the local div		
	- 500·	- 15
_	400	- 10
	300	10
	200 -	— 15
_	- 150	- 10
	- 100	— 10
	- 75	- 10
_	50 ·	- 10

3.0 % Agarose

 $5~\mu l$ loaded onto 3.0 % agarose

For general laboratory use.

Shipping: shipped on gel packs

Storage Conditions: store at -20 °C

Additional Storage Conditions: store dark

Short term storage (up to 1 month) at 4 °C possible.

Shelf Life: 12 months

Form: liquid, DNA fragment mix in 10 mM Tris-HCl pH 7.5, 10 mM EDTA, 8 % (w/v) Glycerol, SYBR[®] Green, Tartrazine and Xylene Cyanol FF

Color: green

Concentration: 120 ng/µl

Description:

Fluorescent Low Range DNA Ladder consists of 11 DNA fragments ranging from 50 bp to 1 kb. It is designed to show virtually uniform spacing over a wide fragment range. The ladder allows sizing and concentration estimate of DNA fragments on agarose gels generated by PCR or restriction digest. The prestained fragment mix is supplied in ready-to-use format containing SYBR® Green fluorescent DNA stain and orange / blue tracking dyes.

Fluorescent DNA Stain:

DNA Ladders with Fluorescent Stain contain SYBR® Green a fluorescent DNA intercalator dye specially developed for DNA analysis applications. High quantum yield and excellent stability makes SYBR® Green the ideal fluorophore for DNA staining applications and a superior replacement for Ethidium Bromide.

DNA Ladders with Fluorescent Stain are optimized for direct loading into unstained agarose gels and are recommended for use in combination with Gel Loading Buffer with DNA Stain (#PCR-274 - #PCR-276).

The ladders provide highest convenience during routine handling and avoid commonly used gel stains like Ethidium Bromide.

Recommended Load:

5 µl per lane

DNA Fragments:

50, 75, 100, 150, **200**, 300, 400, **500**, 600, 800, 1000 bp

